

Round Fluted Aluminum Column

6"x10'-0"

w/ Standard Cap & Base

SKU: Col-RD0610WHT Cap/Base-RDSTD06WHT

Product Material: Aluminum

Notes

- Tolerances: +/- 1/4" in all dimensions
- Whole columns must have 75% contact at the top and 100% contact at the bottom. For split columns, leave a 1/2" - 1" gap between the top of the column and the header. See Installation Instructions.
- Column must be primed and painted after installation on jobsite. Follow paint manufacturer's instructions for priming and finishing.
- 6" round Aluminum column has a load bearing capacity of 20,000 lbs max. Once the column is split it has NO load bearing capabilities.
- Top of column is attached to header with a flashing cap. Bottom of column is attached to substrate with 'L' brackets when using a standard cap/base set. See installation instructions for guidance.
- Column inside dimensions:
4-15/16"
- *Inside dimensions have an 1/8" tolerance*
- Columns are not intended to be used in a free standing application without the use of a tie down system.

Drawn by: CAG
Date: 13 May 2019
Scale: NTS 6x10-RD0610WHT



Building Products

1015 Brundidge Blvd.
P.O. Box 589
Troy, Alabama 36081
334.566.5000
Fax 334.566.4626
www.hbgcolumns.com

©2018 HB&G Building Products, Inc.

