6" Balustrade System

# 3-1/2" Sherwood

Baluster

## SKU: 58061

## Product Material: Polyurethane/cPVC

## Notes

- The Sherwood balusters are produced using EMT surrounded with a high density polyurethane filler
- All balustrade parts come primed and ready to paint from the factory.
- Balusters are connected to top & bottom rails by drilling holes into the top & bottom rails and inserting the galvanized pipe through. See Installation Instructions.
- Sherwood Baluster length & on center dimension:
58061 - 28" - 5-1/4" O.C. Max
58062 - 31" - 5-1/4" O.C. Max
58063 - 36" - 5-1/4" O.C. Max
- Balusters have 3/4" EMT pipe inside for sturctural stability.
- HB&G is not responsible for any balustrade system that does not meet the requirements of the governing building code in the location where the system is installed.
- All balustrade parts come primed and ready to paint from the factory.
- Balustrade is attached to a structural newel, column, or wall using our installation kits. Rail must be attached to a structural newel, column, or wall. See Installation Instructions.
- HB&G is not responsible for any balustrade system that does not meet the requirements of the governing building code in the location where the system is installed.
- Balustrade must be primed and painted after installation on jobsite. If balustrade is not primed and painted it will turn a yellowish color due to UV rays. DO NOT paint balustrade using dark colors (dark colors are considered any color that falls within the L values of 56 to 0). Follow paint manufacturer's instructions for priming and finishing.




| | |
|---|---|
| Drawn by: | CAG |
| Date: | 15 May 2019 |
| Scale: | NTS |

HB&G Building Products
1015 Brundidge Blvd.
P.O. Box 589
Troy, Alabama 36081
334.566.5000
Fax 334.566.4626
www.hbgcolumns.com