7" Balustrade System

5-1/4" Calvert

Baluster

SKU: 58041

Product Material: Polyurethane/cPVC

Notes

- The Calvert balusters are produced using a galvanized steel pipe surrounded with a high density polyurethane filler.
- All balustrade parts come primed and ready to paint from the factory. Follow paint manufacturers instructions for priming and finishing.
- Balusters are connected to top & bottom rails by drilling holes into the top & bottom rails and inserting the galvanized pipe through. See Installation Instructions.
- Calvert baluster lengths & on center dimensions:
58041 - 23" - 6-1/2" O.C. Max
58045 - 29" - 6-1/2" O.C. Max
58042 - 35" - 6-1/2" O.C. Max
- Balusters have a 2" galvanized pipe inside for structural stability.
- HB&G is not responsible for any balustrade system that does not meet the requirements of the governing building code in the location where the system is installed.
- The 7" balustrade system is produced using a PVC pipe surrounded by a high density polyurethane foam.
- Top & Bottom Rails come in lengths of 8'-0",10'-0", & 12'-0" lengths. A support block should be used every 4'-0" span.
- All balustrade parts come primed and ready to paint from the factory.
- Balustrade is attached to a structural newel, column, or wall using our installation kits. Rail must be attached to a structural newel, column, or wall. See Installation Instructions.
- Balustrade sections can NOT be connected end to end. Top & bottom rails must connect to a structural member.
- Rail Dimensions:
Top Rail: 7-1/4" wide x 5-1/2" high
Bottom Rail: 7-1/4" wide x 5-1/2" high



Drawn by:	CAG
Date:	15 May 2019
Scale:	NTS

HB&G Building Products
1015 Brundidge Blvd.
P.O. Box 589
Troy, Alabama 36081
334.566.5000
Fax 334.566.4626
www.hbgcolumns.com